

ETS-1010Series

Media Converter

10G SFP + Port to 10GBase-Tx

RoHS Compliant



Description

This product is high-performance 10G optical media converter , Using Optical - Electrical wavelength conversion, realize the optical signal equilibrium amplification, clock extraction and optical regeneration, and with WDM (DWDM/CWDM) technology, can achieve optical signals transmit in a single fiber by single or multiple way over a long distance. On the existing network infrastructure, it can quickly improve the communication capacity, expand the bandwidth, while using low cost and high cost-effective solutions to manage and operate the system, easy operation and maintenance.

Main Features

- Support Jumbo Frame
- Transparent Transport and very low delay
- Support ITUT prescribed DWDM/CWDM wavelength
- Support Loopback test function
- Support hot plugging
- Full State Led display
- Supports auto MDI/MDIX function
- Status LED for easy monitoring of device status
- FCC Class A & CE approved



Specifications

Interface

- 1 x Ethernet port (RJ45) 10GBase-Tx
- 1 x Optical port (SFP+) 10GBase-Fx

Optical Port

- Transfer Distance: up to 80km;
- Connectors: SFP+
- Fiber core: 9/125um on single mode fiber, 50/125 um and 62.5/125 um on multi-mode fiber

Ethernet Port

- Available speed: force 10Gbps Full-Duplex and Half-Duplex auto-negotiation
- Connectors: RJ-45 Connector; MDI/MDI-X connection auto-sensing

Standard

- IEEE802.3an(10Gbase-T),
- IEEE802.3ae(10Gbase-SR/LR/ER/ZR)

Power Requirement

- Input: 5V DC

Physical Characteristics

- Housing: Metal enclosure
- Dimensions: 140 x 100 x 30mm
- Weight: 0.65kg

Environmental Limits

- Operating Temperature: -10°C to 70°C
- Storage Temperature: -20°C to 70°C
- Operating Humidity: 10% to 90% RH
- Storage Humidity: 5% to 90% RH

Agency Approvals

- FCC Part 15 of Class A & CE approved

Warranty

- 3 years

Ordering Information

ETS-1010S	10G SFP+ Fiber port to 10GBase-T
-----------	----------------------------------

Important Notice

Performance figures, data and any illustrative material provided in this data sheet are typical and must bespecifically confirmed in writing by ENTA SOURCE before they become applicable to any particular order or contact.In accordance with the ENTA SOURCE policy of continuous improvement specifications may change without notice.

The publication of information in this data sheet does not imply freedom from patent or other protective rights of ENTA SOURCE or others. Further details are available from any ENTA SOURCE sales representative.