

Specification

ETS
ENTA SOURCE CO., LTD.

ETN9075-2GX8PGT



**2*1000M SFP, 8*10/100/1000M RJ45, IP40
Industrial managed switch (PoE)**

Contact US

LINE@ @ets.online

087-412-2552



Main Features

2*1000Base-X, 8*10/100/1000Base-T

Industrial Ethernet PoE Switches

Input Voltage: DC48-58V(PoE)

Operating Temperature: -40°C ~ +75°C

Shell: IP40 protection, fanless design

Test Report: CCC, RoHS, FCC, CE

Anti-static: 8KV-15KV

MTBF: 100000 Hours

PRODUCT DESCRIPTION

This device is 2*1000Base-X & 8*10/100/1000Base-T Industrial Ethernet PoE Switches. Through the fanless heat dissipation circuit design, wide range of working environment temperature, high protection level and other technologies, it provides excellent industrial quality with high/low temperature resistance and lightning protection, and enhances the reliability and safety of industrial networks. It can better meet the deployment requirements of rail transit, safe city, intelligent transportation, outdoor monitoring and other harsh environments.

ETN9075-2GX8PGT

PRODUCT PARAMETERS


Provider Mode Ports	
Fixed port	2*1000 Base-X, 8*10/100/1000Base-T
Power interface	Phoenix terminal, redundant dual power supply
LED indicators	PWR, OPT, NMC, ALM
DIP Switch	
1 C/D	Remote PD Reset
2 LGY	Stand/Non-standard PoE Mode
3 VLAN	Port isolation
4 RST	Reset
Cable Type & Transmission Distance	
Twisted pair	0 100m (CAT5e,CAT6)
Monomode optical fiber	20/40/60/80/100KM
Multimode (optical) fiber	550m
Network Topology	
Ring topology	Unsupported
Star topology	Support
Bus topology	Support
Tree Topology	Support
Hybrid topology	Support
Electrical Specifications	
Input voltage	DC48~58V(PoE)
Total Power consumption	<246W(PoE)
Voltage Alarm	Support
PoE Support	
PoE port	1~8
PoE Protocol	802.3af, 802.3at
Pin Assignment	1,2,3,6
PoE Mode	Standard & non-standard are supported
Remote PD Reset	Support
Layer 2 Switching	
Switching capacity	26G
Packet forwarding rate	1934Mpps
MAC address table	16K
Buffer	2M
Forwarding delay	<5us
MDX/MIDX	Support
Flow control	Support
Jumbo Frame	Support 10K Bytes
WatchDog	Support
Port isolation	Support

ETN9075-2GX8PGT

Environment	
Operating temperature	-40°C ~ +75°C The device is tested for 4 hours at temperatures in 85°C
Storage temperature	-40°C ~ +85°C
Relative humidity	5% ~ 95% non-condensing
Thermal methods	Fanless, natural cooling
MTBF	100,000 hours
Mechanical Dimensions	
Product size	143X104X48mm
Installation Method	DIN rail
Weight	0.5KG around
EMC & Ingress Protection	
IP Level	IP40
Surge protection of Power	IEC 61000-4-5 Level X (6KV/6KV) (8/20us)
Surge protection of Ethernet port	IEC 61000-4-5 Level X (4KV/4KV) (10/700us)
RS	IEC 61000-4-3 Level 3 (10V/m)
EFI	IEC 61000-4-4 Level 3 (1V/2V)
CS	IEC 61000-4-6 Level 3 (10V/m)
PFMF	IEC 61000-4-8 Level 4 (30A/m)
DIP	IEC 61000-4-11 Level 3 (10V)
ESD	IEC 61000-4-2 Level 4 (8K/15K)
Free fall	0.5m
Authentication	
Authentication	CCC, CE, FCC, RoHS
Accessories	
Accessories	Device, Terminals, Specification, Certificate, power adapter(optiona)

ETN9075-2GX8PGT

SIZE AND APPEARCE



ENTA SOURCE reserves the right to make changes to the products or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such products or information.
Published by ENTA SOURCE Co.,Ltd.
Copyright © ENTA SOURCE
All Rights Reserved